

SONANCE 



BPS6 THIN-LINE SUBWOOFER



BPS6 TL

Sonance is proud to announce the BPS6 TL, the first ever Discreet Opening Thin-line Subwoofer. Created for Architectural Series and Visual Performance Series, this in-wall or in-ceiling subwoofer is designed for tight spaces with restricted mounting depths.



BPS6 TL
SKU 93324

Woofers:	13" (330mm) x 3" (76mm) Laminated Carbon Fiber Cone with a Rubber Surround, Dual Voice Coil
Frequency Response:	38Hz - 125Hz ±3dB
Impedance:	6 Ohms nominal
Power Handling:	50 Watts minimum; 150 Watts maximum
Sensitivity:	87dB @ 2.83V / 1 meter
Dimensions: (H x W x D)	39 3/8" x 11" x 3 3/8" (1000mm x 279mm x 86mm)
Port Tube Dimensions: (Dia. x L)	3" x 15" (76mm x 381mm)



**Architectural Series
Bandpass Connector**
SKU 93335



**Visual Performance Series
Bandpass Connector**
SKU 93334

Bandpass Connector:	ASBPC3RS TL	VPBPC3R TL
Dimensions: (Dia. X D)	3 7/8" x 2 1/4" (99mm x 57mm)	4 5/16" x 3 1/2" (109mm x 89mm)
Grille Dimensions: (Dia.)	ASBPC3RS TL shipped with Round 4" (102mm) and Square 4" (102mm) perforated steel grilles	VPBPC3R TL shipped with Round 4 29/32" (124mm) perforated steel grilles
Mounting Platforms:	SKUs 93362, 93363, 93364, 93365, 93366	—